

Safety Data Sheet

Section 1: Identification of the Substance/Preparation and of the Company/Undertaking

Product Name: ALL THAT JAZZ - Double Top - Top Coat for Glitter
Chemical Name: Nail Enamel

SDS Prepared 1/26/2018
SDS Updated N/A
Revision 00

Product Use: cosmetics

Supplied by: All That Jazz
Los Angeles, CA

Product # : 40003

Emergency Phone Number: (800) 535-5053
Information Contacts: (714) 773-9758

Section 2: Hazards Identification

GHS Classifications

Physical
Flammable Liquids, Gategory 2

GHS Label:



Hazard Statements

H224: Extremely flammable liquid and vapour.

Precautionary Statements

Prevention

P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233: Keep container tightly closed.
P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: Liquid
IMMEDIATE CONCERNS: Highly Flammable

POTENTIAL HEALTH EFFECTS

EYES: Mildly to moderately irritating
SKIN: Mild skin irritant
SKIN ABSORPTION: May cause dermatitis by defatting the skin from prolonged contact.
INGESTION: Causes gastro-intestinal irritation, nausea, vomiting and diarrhea.
INHALATION: • Prolonged inhalation may be harmful
• Can cause drowsiness, headaches, nausea, vomiting and narcosis
• May cause lung irritation

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Overexposure in eyes may cause redness, itching and watering
SKIN: Symptoms of skin overexposure in some sensitive individuals may include redness, itching and irritation of affected area
SKIN ABSORPTION: None known
INGESTION: May cause irritation of the digestive track
INHALATION: May cause drowsiness, dizziness, headaches and nausea

ACUTE TOXICITY:

Eyes: Mild to moderate irritation to eyes near affected area
Skin: Mild to moderate irritation to skin near affected area
Inhalation: High concentrations of vapors can cause drowsiness, dizziness, headaches and nausea

CHRONIC EFFECTS:

None known

CARCINOGENICITY: Not classifiable as a human carcinogen by the IARC

MUTAGENICITY: This product is not reported to produce mutagenic effects in humans

REPRODUCTIVE TOXICITY

REPRODUCTIVE EFFECTS: This produce is not reported to cause reproductive effects in humans
TERATOGENIC EFFECTS: This product is not reported to produce Teratogenic effects in humans

MEDICAL CONDITIONS AGGRAVATED:

None known

ROUTES OF ENTRY: Eye contact, Inhalation

TARGET ORGAN STATEMENT: Eyes, skin and respiratory system

Section 3: Composition/Information on Ingredients

INCI Name	CAS#	EINECS#	Exposure OSHA TWA/STEL	Limits ACGIH TWA/STEL	Carcinogen IARC/NTP/OSHA	%
Isobutyl Acetate	110-19-0	203-745-1	150 ppm	150ppm	Not Listed	40-50
Ethyl Acetate	141-78-6	205-500-4	400 ppm	400 ppm	Not Listed	20-25
Isopropyl Alcohol	67-63-0	200-661-7	400 ppm	400 ppm	Not Listed	5-10
Methyl Ethyl Ketone	78-93-3	201-159-0	200 ppm	200 ppm	Not Listed	0-3
Xylene	1330-20-7	215-535-7	100 ppm	100 ppm	3/no/no	<1

N/E - None Established

N/DA - No Data Available

* See section 16

N/R - Not Reviewed

N/A - Not Applicable

Ethyl Acetate : Hazardous Symbol: F; Xi

Risk phase: R11, R36, R66,R67 - Safety Phase: S2, S16, S26,S33

Isobutyl Alcohol: Hazardous Symbols F, Xi
 Isopropyl Alcohol: Hazardous Symbol: F, Xi
 Methyl Ethyl Ketone : Hazardous Symbols: Xi, F-

Risk phase: R11, R36,R67 - Safety Phase: S2,S16, S23, S25, S29,S33
 Risk phase: R11,R36, R67 - Safety Phase: S2, S7, S16, S24/25, S26
 Risk phase: R11,R36,R66, R67 - Safety Phase: S2, S9, S16

Section 4: First Aid Measures

First Aid for Eye: If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention

First Aid for Skin: Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention

First Aid for Inhalation: Remove to fresh air. If breathing is difficult, administer oxygen. If symptoms persist, seek medical attention

First Aid for Ingestion: If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with head down. Seek medical attention for advice about weather to induce vomiting. If possible do not leave individual unattended.

Section 5: Fire Fighting Measures

Flash Point (°F/°C)	Flammable Limit (vol%)	Auto-ignition Temperature (vol%)
68°F / 20°C Estimated	400ppm	750°F -900 °F
Method:		
Extinguishing Media: Foam or dry chemical, cold water spray		
Fire Fighting Instructions: Wear self-contained breathing apparatus and protective clothing. USE WATER WITH CAUTION. Use water spray to keep fire-exposed container cool. Water may be ineffective in fighting the fire, Fight fire from a distance and protective location.		
Unusual Hazardous: Flammable. When expose to heat and flame, material is a fire explosion hazard. It may produce toxic products CO, Carbon dioxide and oxides of Nitrogen. Vapor may cause a flash fire or ignite explosively. Vapors may travel considerable distance to a source of ignition and flash back. Prevent building up vapor or gases to explosive concentrations		

Section 6: Accidental Release Measures

Spill or Release Procedures: Eliminate all sources of heat and ignition. Use absorbent material for spills and dike it, wash spill material into retaining containers. Place container in a well ventilated area. Consult an expert on disposal of recovered materials and ensure conformity to local disposal regulations. Keep unnecessary and unprotected personnel from entering. Contained and remove liquid when possible. Use non-sparking tools and equipment. Collect liquid in appropriate container or absorb with an inert material, (e.g. vermiculite, dry sand, earth) and place in a chemical water container. Do not use combustible materials such as sawdust. Do not flush to sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations require the consultation of Directive 98/24/EC. Dispose and report per regulatory requirements if necessary. Please prevent washings from entering waterways.

Section 7: Handling and Storage

Handling: No smoking
 Keep container cool and dry. Keep away from heat, light and ignition sources. Avoid breathing high vapor concentrations. Avoid prolonged or repeated contact with skin. Use only with adequate ventilation. Wash thoroughly after handling

Storage: Keep containers tightly closed when not in use.
 Store in well ventilated area. Store @ 70 °F +/- 15 °F (21°C +/- 8°C), allow some air space above liquid level.

Special precautions: Vapor is heavier than air, spreads along the ground or may be move by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking or other sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty)because product (even just residue) can ignite explosively.

Section 8: Exposure Controls / Personal Protection

Engineering Controls: Facilities storing or utilizing this material should be equipped with an eye facility and safety shower. Use process enclosures local exhaust ventilation, or other engineering tools to control airborne levels below recommended exposure limits. Use explosion -proof ventilation equipment.

Personal Protective Equipment General: To identify additional Personal protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product. Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron boots, or whole body suits. Nitrile rubber is better than PVC.

Eye / Face Protection: Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations permit other types of safety glasses

Skin Protection: Wear resistant gloves. To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

Respiratory Protection: A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by nuisance level organic vapor dust masks can be used, however the use of the respirator is limited. Follow OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149.

Section 9: Physical and Chemical Properties

Appearance	Odor & Odor Threshold	pH	Specific Gravity	Viscosity	% Volatile	
clear, viscous liquid	fruity ester odor	NA	(H20=1): 0.94	N/DA	W/W %:99+	
Boiling Point/Freezing Point	Decomposition Temperature	Octane/Water Partitioning Coefficient Log Po/w	Vapor Pressure:	Evaporation Rate	Ignition	Solubility In Water (20°C)
170°F (77°C)	N/A	N/A	N/A	No Data	No Data	Insoluble
Flash Point (°F/°C)	Flammable Limit (vole%)	Auto-ignition Temperature (vol%)				
68°F / 20°C Estimated	400 ppm	No Data				

Section 10: Stability and Reactivity

Stability: Stable.
Incapability (Material to Avoid): Avoid oxidizing agents, acids and bases (heat)

Hazardous Decomposition Products: Heated materials produce NO₂, CO₂, CO
Hazardous Polymerization: May occur

Conditions to Avoid: Heat, flame, ignition sources

Section 11: Toxicological Information

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation - skin/eyes
No info available	No info available	No info available	No info available
Further hazardous properties cannot be excluded. The product should be handled with care when dealing with chemicals.			
Sensitization	Mutagenicity	Sub-chronic Toxicity	
No info available	No info available	No info available	

Section 12: Ecological Information

Ecotoxicological Information

Acute Toxicity to aquatic life	Acute Toxicity to plants and animals	Acute Toxicity to Algae	Bioconcentration	Toxicity to Sewage Bacteria
No Information Available	No Information Available	No Information Available	No Information Available	No Information Available
Chemical Fate Information				
Biodegradability		No Information Available		
Chemical Oxygen Demand		No Information Available		

To the best of our knowledge, the ecotoxicological and chemical fate properties have not been thoroughly investigated.
Do not allow to enter drinking water supplies, wastewater, or soil.

Section 13: Disposal Considerations

Dispose of diking materials and absorbent in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition; do not cut, drill, or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate. Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements. For EU Member State, please refer to any relevant Community provisions relating to waste. In their absence, it is useful to remind the user that national or regional provisions may be in force.

Section 14: Transport Information

DOT (49 CFR 172)

Excepted Quantity (49 CFR -173.4a) (≤ 30 ml)
Consumer Commodity, ORM-D (≤ 1.0 L)
UN1263 Paint ,3,II (>1.0 L)

IATA (AIR):

Excepted Quantity (Air Shipper 4.1.2) (≤ 30 ml)
Consumer Commodity,9, ID8000 (≤ 0.5 L)
UN1263 Paint ,3,II (> 0.5 L)

IMDG (OCN):

Excepted Quantity (2008 IMO -3.5.1) (≤ 30 ml)
UN1263 Paint ,3,II LTD QTY(≤ 1.0 L)
UN1263 Paint ,3,II (> 1.0 L)

TDGR (Canadian GND):

Mark Package "Limited Quantity" or "Quantite Limitee" or "LTD QTY" or "Quant Ltee" (≤ 1.0 L)
UN1263, Paint related material, 3, II, (>1.0 L)

ADR/RID (EU):

UN 1263, Paint Related Material,3,II,ADR

MEXICO (SCT):

UN1263, Pintura,3,II, Cantidad Limitada (≤ 1.0 L)

ADGR(AUS):

UN1263, Paint, 3, II LTD QTY (≤ 1.0L)

Section 15: Regulatory Information

US Federal Regulations

Clean Air Act: HAP/ODS	This product contains the following hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act: <ul style="list-style-type: none"> Methyl Ethyl Ketone, CAS # 78-93-3 Xylene CAS # 1330-20-7 There are no ODS's (ozone depleting substances) as defined by the defined by the US Clean Air Act
Clean Water Act: Priority Pollutant	This product contains the following Hazardous Substances as defined by the CWA: <ul style="list-style-type: none"> Xylene CAS # 1330-20-7 Isobutyl Acetate CAS # 110-19-0 This product does not contain any substances that are a Priority Pollutant or Toxic Pollutant under the CWA
FDA:	This product has not been cleared by the FDA for use in food packaging and/or other applicants as an indirect food additive
OSHA	This product is considered to be hazardous under OSHA Hazard Communication Standard. Its hazards are: <ul style="list-style-type: none"> Fire hazard Immediate (acute) health hazard
RCRA	This product contains chemicals considered to be hazardous waste under RCRA (40 CFR 261): <ul style="list-style-type: none"> Ethyl Acetate CAS# 141-78-6, RCRA Code U112 Methyl Ethyl Ketone, CAS # 78-93-3, RCRA code D035,U159 Xylene CAS # 1330-20-7 RCRA Code : U239
SARA Title III: Section 302	This product contains no chemicals regulated under sec 302 as extremely hazardous substances that carry TPQ
SARA Title III: Section 304	This product contains chemicals regulated under section 304 as extremely hazardous chemicals for emergency release notification (CERCLA list): <ul style="list-style-type: none"> Ethyl Acetate CAS# 141-78-6, RQ (lbs) 5000 Xylene CAS # 1330-20-7, RQ (lbs): 100 Methyl Ethyl Ketone, CAS # 78-93-3, RQ (lbs) 5000 Isobutyl Acetate CAS # 110-19-0, RQ (lbs) : 5000
SARA Title III: Section 311-312	This product is considered to be hazardous under OSHA Hazard Communication Standard. And is regulated under section 311-312(40CFR 370): <ul style="list-style-type: none"> Fire hazard Immediate (acute) health hazard
SARA Title III: Section 313	This product contains the following chemicals which are subject to the reporting requirements of section 313 of title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372 <ul style="list-style-type: none"> Methyl Ethyl Ketone, CAS # 78-93-3 Xylene CAS # 1330-20-7 Isobutyl Acetate CAS # 110-19-0
TSCA Inventory Status:	This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA premature notification requirements. None of this chemicals in this material have a SNUR under TSCA

State Regulations:

Ingredients in this mixture are found on the following state criteria list:

CA Right-to-Know Law:	Ethyl Acetate CAS # 141-78-6,Xylene CAS # 1330-20-7, Isopropyl Acetate -CAS# 110-19-0, Methyl Ethyl Ketone- CAS # 78-93-3,	Isobutyl Alcohol CAS # 67-63-0
Massachusetts Hazardous Substances List	Ethyl Acetate CAS # 141-78-6,Xylene CAS # 1330-20-7, Isopropyl Acetate -CAS# 110-19-0, Methyl Ethyl Ketone- CAS # 78-93-3,	Isobutyl Alcohol CAS # 67-63-1
Minnesota Hazardous Substances List	Ethyl Acetate CAS # 141-78-6,Xylene CAS # 1330-20-7, Isopropyl Acetate -CAS# 110-19-0, Methyl Ethyl Ketone- CAS # 78-93-3,	Isobutyl Alcohol CAS # 67-63-2
NJ Right-to-Know Law:	Ethyl Acetate CAS # 141-78-6,Xylene CAS # 1330-20-7, Isopropyl Acetate -CAS# 110-19-0, Methyl Ethyl Ketone- CAS # 78-93-3,	Isobutyl Alcohol CAS # 67-63-1
PA Right-to-Know Law:	Ethyl Acetate CAS # 141-78-6,Xylene CAS # 1330-20-7, Isopropyl Acetate -CAS# 110-19-0, Methyl Ethyl Ketone- CAS # 78-93-3,	Isobutyl Alcohol CAS # 67-63-1

Section 16: Other Information

International Regulations:

Canadian Regulations:
 Ethyl Acetate CAS# 141-78-6 is on the DSL list. WHMIS= B2,D2B
 Xylene CAS # 1330-20-7- on DSL. WHMIS= n/da
 Hydroxypropyl Cellulose CAS # 9004-64-2 on DSL. WHMIS = n/da
 Isobutyl Acetate CAS # 110-19-0- on DSL- WHMIS= n/da
 Methyl Ethyl Ketone, CAS # 78-93-3, is on the DSL list. WHMIS B2, D2A
 Isopropyl Alcohol- CAS# 67-63-0 is on the DSL list . WHMIS= B2.D2B

67/548/EU Requirements:

European Community:



EU Classes and Risk / Safety Phrases :

● **HAZARDOUS SYMBOLS:**

F - Highly Flammable

Xn- Harmful

● **RISK PHRASES:**

R11 Highly Flammable

R20/22: Harmful by inhalation and if swallowed

R36/38/37 Irritating to eyes, respiratory system, and skin

● **SAFETY PHRASES:**

S7 Keep container tightly closed

S9 Keep container in a well-ventilated place

S16 Keep away from sources of ignition-No Smoking.

S24/25: avoid contact with skin and eyes

S33 Take precautionary measures against static discharges

S37/S39 Wear suitable gloves and eye/face protection

S45 In case of accident or if you feel unwell seek medical advice immediately (show the label where possible)

EU Classes and Risk / Safety Phrases for Referenced Ingredients (see section2) :

● **HAZARDOUS SYMBOLS:**

F - Flammable Substance or preparation

Xi = Irritant

● **RISK PHRASES:**

R11: Highly flammable

R36: Irritating to eyes

R66: Repeated exposure may cause skin dryness or cracking

R67: Vapours may cause drowsiness and dizziness

● **SAFETY PHRASES:**

S2 Keep out of reach of children

S7 Keep container tightly closed

S9 Keep container in a well-ventilated place

S16 Keep away from sources of ignition-No Smoking.

S23: Do not breathe gas/fumes/vapour/spray

S24/25: avoid contact with skin and eyes

S25: Avoid contact with eyes


S26 In case of contact with eyes, rinse immediately with plenty of water and seek advice

S29: Do not empty into drains

S33 Take precautionary measures against static discharges

Hazard Rating System (Pictograms)

NFPA:



HMIS:

HEALTH	<input type="checkbox"/>
FLAMMABILITY	<input type="checkbox"/>
REACTIVITY	<input type="checkbox"/>
PERSONAL PROTECTION	<input type="checkbox"/>

This information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage use or disposal of the product. This SDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the SDS may not be applicable. If there are any problems or concerns understanding this SDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at (1-800-535-5053).

Mariana Arias
 Regulatory Manager