

SAFETY DATA SHEET

MUNDO PRODUCT REMOVER

Page 1 of 3

Revision 0

Revision date

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name PRODUCT REMOVER
Company Rouse Marketing Ltd
Whetstone Barn
Bayton Lane
Horsforth
Leeds
LS18 5EZ
Telephone 0113 258 5540

2. HAZARDS IDENTIFICATION

Main hazards Highly flammable. Irritating to eyes. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
Acetone	90 - 100%	67-64-1	200-662-2	F; R11 Xi; R36 R66 R67

4. FIRST AID MEASURES

Skin contact Repeated exposure may cause skin dryness or cracking. Wash off immediately with plenty of soap and water. Seek medical attention if irritation or symptoms persist.

Eye contact Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention.

Inhalation Vapours may cause drowsiness and dizziness. Move the exposed person to fresh air. Seek medical attention if irritation or symptoms persist.

Ingestion DO NOT INDUCE VOMITING. Seek medical attention if irritation or symptoms persist.

5. FIRE FIGHTING MEASURES

Extinguishing media Alcohol resistant foam. Carbon dioxide (CO2) Dry chemical. Sand. Water spray.

Fire hazards Vapour may travel considerable distance to source of ignition and flash back. Burning produces irritating, toxic and obnoxious fumes

Protective equipment In case of fire and/or explosion do not breathe fumes. Wear suitable respiratory equipment when necessary.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Eliminate all sources of ignition. Vapour may travel considerable distance to source of ignition and flash back. Ensure adequate ventilation of the working area. Surfaces contaminated with the product will become slippery. Wear suitable protective equipment.

Environmental precautions Advise local authorities if large spills cannot be contained. Do not allow product to enter drains. Do not let product contaminate subsoil. Prevent further spillage if safe.

Clean up methods Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal.

7. HANDLING AND STORAGE

Handling	Keep away from sources of ignition - No smoking. Avoid sparks, flames, heat and sources of ignition. Take precautionary measures against static discharges. Do not breathe gas/fumes/vapour/spray. Do not eat, drink or smoke in areas where this product is used or stored. Ensure adequate ventilation of the working area. Wear suitable protective equipment.
Storage	Keep out of the reach of children. Keep container tightly closed and in a well-ventilated place. Store in a cool, dry area. Do NOT allow to freeze.
Suitable packaging	Plastic containers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits		
Acetone	WEL 8-hr limit ppm: 500 WEL 15 min limit ppm: 1500	WEL 8-hr limit mg/m ³ : 1210 WEL 15 min limit mg/m ³ : 3620
Respiratory protection	Do not breathe gas/fumes/vapour/spray. An air-fed mask is recommended.	
Hand protection	Neoprene gloves.	
Eye protection	In case of splashing, wear: Approved safety goggles. Provide eye wash station.	
Protective equipment	Adopt best Manual Handling considerations when handling, carrying and dispensing. Wear suitable protective equipment.	

9. PHYSICAL AND CHEMICAL PROPERTIES

Description	Liquid.
Colour	Clear.
Odour	Characteristic.
Boiling point	56°C
Flash point	-18°C
Relative density	0.80
Water solubility	soluble in water

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions. Will not decompose if stored and used as recommended.
Conditions to avoid	Heat, sparks and open flames. Heating produces hazardous fumes. Do NOT allow to freeze.
Materials to avoid	Organic materials. Strong acids and strong bases. Strong oxidising agents.
Hazardous decomposition Products	Carbon oxides. Toxic fumes.

11. TOXICOLOGICAL INFORMATION

Acute toxicity	Vapours may cause drowsiness and dizziness.
Corrosivity	Irritating to eyes.
Sensitization	No sensitization effects reported.
Repeated or prolonged exposure	Repeated exposure may cause skin dryness or cracking.
Mutagenic effects	No mutagenic effects reported.
Carcinogenic effects	No carcinogenic effects reported.
Reproductive toxicity	No teratogenic effects reported.

12. ECOLOGICAL INFORMATION

Ecotoxicity	No data is available on this product.
Degradability	Evaporates readily.
Bioaccumulation	Does not bioaccumulate.

13. DISPOSAL CONSIDERATIONS

General information	Contact a licensed waste disposal company. Dispose of as special waste in compliance with Local and national regulations.
Disposal methods	For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used.
Disposal of packaging	Empty containers can be sent to landfill after cleaning, if in compliance with Local and national regulations.

14. TRANSPORT INFORMATION

ADR/RID	UN 1090 Packing group II Class 3 Hazard ID 33 Proper Shipping Name ACETONE.
IMDG	UN 1090 Packing group II Class 3 Marine pollutant No EmS Code F-E S-D
IATA	UN 1090 Packing group II Class 3 Subsidiary risk - Packing Instruction (Cargo) 307 Maximum quantity 60 L Packing Instruction (Passenger) 305 Maximum quantity 5 L

15. REGULATORY INFORMATION

Symbols	F - Highly flammable; Xi - Irritant
Risk phrases	R11 - Highly flammable. R36 - Irritating to eyes. R66 - Repeated exposure may cause skin dryness or cracking R67 - Vapours may cause drowsiness and dizziness.
Safety phrases	S16 - Keep away from sources of ignition - No smoking.

16. OTHER INFORMATION

Text of risk phrases in Section 3	R11 - Highly flammable R36 - Irritating to eyes. R66 - Repeated exposure may cause skin dryness or cracking. R67 - Vapours may cause drowsiness and dizziness.
Further information	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.

